Distance Measurement	Range *1	5000m
with Reflector Distance Measurement	Accuracy	±(2+2ppmxD)mm
	Measure Interval	Fine: 0.3s, Tracking: 0.1s
	Range *2	1000/1500/2000m Optional
without Reflector	Accuracy	±(3+2ppmxD)mm
	Measure Interval	0.3-3s
Angle Measurement	Accuracy	2"
	Measure Method (HZ/V)	Absolute Continuous, Diametrical
	Diameter of Encoder Disk	79mm
	Display Resolution	0.1"
	Compensation	Liquid, Dual Axis Compensation
	Compensator Setting Accuracy	1"
	Compensator Range	±4'
Telescope	Image	Erect
	Tube Length	154mm
	Effective Aperture	45mm (EDM:50mm)
	Magnification	30x
	Resolving Power	3"
	Field of View	1°30"
	Focusing Range	1.2m
	Reticle	Illuminated, 4 Brightness Level
Vial	Plate Vial	30"/2mm
	Circular Vial	8'/2mm
Laser Plummet	Туре	Laser Point, 4 Brightness Level
(Default)	Accuracy	±1.5mm at 1.5M Instrument Height
	Wavelength	630-670nm
	Laser Class	Class 2 /IEC60825-1
	Laser Power	<0.4mW
System Config	Operating System	Android 11.0
	Processor	MT6762
	Internal Memory	RAM: 4GB; ROM: 64GB
Communication	Interfaces	- USB Type C (OTG)
		- TF Card
	Network	3G 2100/900 CDMA BC0 TDSCDMA A/F
		4G LTE band1/3/7/38/39/40/41
	Bluetooth	Bluetooth 4.0
	WLAN	Dual-Band Single Stream 802.11 a/b/g/n RF for Data Li
	Microphone / Speaker	Available
Display	Туре	5.5 Inch, TFT LCD Screen, 720*1280
Battery	Туре	Lithium-lon, 7.4V
	Operating Time	8 Hours
Dimension	Size	350mm*170mm*217mm
	Weight	5.7kg
Environmental	Temperature Range (Operation)	-20°C ∼ 50°C
	Protection	IP55

^{*1:} Good conditions (good visibility approx.40km, overcast, twilight)



SOUTH SURVEYING & MAPPING TECHNOLOGY CO., LTD.

Add: South Geo-information Industrial Park, No.39, Si Cheng Road, Tian He District,
Guangzhou 510663, China http://www.southinstrument.com



N1

Android Total Station



- New! Android 11.0 Operating System
- Reliable EDM 1000m Non-Prism Range
- High Precision 2", 2+2ppm
- User Friendly with EDM Trigger Key
- 5.5 Inches Color Touchscreen
- Fast, Simple and Flexible Data Transfer
- Intuitive Onboard Software SurvStar



^{*2:} White objects with high reflectivity (KGC 90%)

Android Total Station

N1

With the proven dual-laser technology, N1 features a powerful and reliable EDM module designed for extremely long-range, fast speed and stable measurement, even under the tough conditions.

All these combined in the new-designed colorful touch screen with fast, simple and flexible data transfer, which makes you more productive than ever before.

Reliable and Outstanding EDM

- 1000m/1500m/2000m Non-prism Range Optional.
- 5000m Prism Range.
- Improved the Algorithm by Dual-Laser EDM.

Guaranteed High Precision

- 2" Angle Accuracy.
- 2+2ppm Distance Accuracy.
- Extremely Fast (0.3s) When Getting the Target.

EDM Trigger Key

- Achieve the Target by Only One Simple Button Press.
- Not Necessary to Taking Your Eyes Off the Telescope.

New Designed Control Panel

- 5.5 Inch Color Touchscreen for Higher Readability.
- User-Defined Numeric and Functional Keys.
- Unique Brightness Sensor with Virtual Button, Which Provides a Smartphone-like Experience.

Fast, Simple and Flexible Data Transfer

- Support USB-Type C, TF Card, SIM Card Slot
- Flexible Data Transfer with Bluetooth and Wi-Fi Technology.

Double-lock Theft Protection

First security protection goes to Android screen locker with 4 options such as PIN/Code/Pattern/Password. Second one will be the compulsory online firmware update (in terms of language option, software key, etc.) every 6 months, without which it's not possible to continue the instrument or program use.

Reliable and Outstanding EDM - 1000m Non-Prism

Guaranteed High Precision - 2", 2+2ppm

User Friendly - EDM Trigger Key

Smartphone-like Experience - Brightness Sensor with 5.5 Inch Touchscreen

Fast, Simple and Flexible Data Transfer



Digitizing Your Work by **Survstar**



Iconic User Interface

The Survstar onboard program features an iconic display of the survey elements, like electronic bubble, e-compass, star key and iconic toolbar. It provides a better understanding for station setup, data collect, stake out in daily tasks.



Map-Driven Workflow

Map is an interactive display feature embedded in Survstar. It offers a graphical display of the survey elements with base map, which can be downloaded by network, or imported by manual.

It provides a better understanding for data collect, stake out in daily tasks.




Powerful Onboard Program

Including Free Station, COGO, CAD Stake Out, Arc Stake Out, Reference Line, Traverse, etc.


CAD Stake Out

With CAD Stake Out, N1 helps to handle the data and stake out freely in DWG or DXF files. The only thing you need to do is import the CAD files to your N1 total station.



Traverse

When you've got a very difficult site with a lot of obstructions like trees, that obscures our visibility; Or when you can't measure or place the points you need, traverse on N1 total station helps to get a few more control points to work further than the first orientation.



Flexible Data Manage

You can send or receive your data to your controller or PC more flexible than ever, by multiple data format, e.g. *.txt, *.dxf, *.dat, *.csv, *xls.

When you've got a N1 total station, you will have infinite possibilities.